

# Leostomer® ER2064

Styrene Butadiene Block Copolymer

Riken Technos Corp.

## Message:

Leostomer® ER2064 is a styrene-butadiene copolymer (SBC) product. It is available in North America or Asia Pacific.

Features include:

- high strength
- Copolymer
- environmental protection/green
- good weather resistance

General Information			
UL YellowCard	E58608-246576		
Features	High tensile strength		
	Copolymer		
	Recyclable materials		
	Good weather resistance		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	0.898	g/cm <sup>3</sup>	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	60		ISO 868
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (300% Strain)	2.60	MPa	ISO 37
Tensile Stress (Yield)	15.0	MPa	ISO 37
Tensile Elongation (Break)	930	%	ISO 37
Tear Strength	30	kN/m	ISO 34-1
Compression Set (70°C, 22 hr)	39	%	ISO 815
Aging	Nominal Value	Unit	Test Method
Change in Tensile Strength in Air (120°C, 168 hr)	-2.0	%	ISO 188
Change in Tensile Strain at Break in Air (120°C, 168 hr)	-1.0	%	ISO 188
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-60.0	°C	ISO 974
Additional Information			

The values listed above are tested in accordance with JIS K test methods.Rebound Resilience: 41%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

