

Orevac® 9314

Ethylene Vinyl Acetate Copolymer

Arkema

Message:

Orevac® 9314 is an Ethylene Vinyl Acetate Copolymer (EVA) product. It can be processed by blown film and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Film.

General Information			
Features	Terpolymer		
Uses	Film		
Forms	Pellets		
Processing Method	Blown Film		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	2.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	55		ISO 868
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	70.0	°C	ASTM D1525
Melting Temperature	90.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT