

TechnoElast V A6000 I 2 sw

Thermoplastic Elastomer
TechnoCompound GmbH

Message:
Good insulation, absorption and elastic properties

General Information			
Appearance	Black		
	Available colors		
	Natural color		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	0.920	g/cm³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 3 sec)	60		DIN 53505
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			
Fracture	4.90	MPa	ISO 527-2/1
100% strain	2.60	MPa	ISO 527-2/50
Tensile Strain (Break)	420	%	ISO 527-2/50
Elastomers	Nominal Value	Unit	Test Method
Compression Set (70°C, 22 hr)	30	%	ISO 815

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT