

Qenos PP PPU 1080

Polypropylene Homopolymer

Qenos Pty Ltd

Message:

PPU 1080 is a high flow injection moulding grade of Polypropylene homopolymer with high flow and high stiffness.
PPU 1080 is intended for use in the manufacture of closures, housewares and food containers. Suitability for use in any application should be determined by appropriate performance testing.
PPU 1080 is suitable for food contact applications and conforms to the requirements of AS2070-1999, Plastics Materials for Food Contact Use.

General Information			
Features	Food Contact Acceptable		
	Homopolymer		
	Medium Flow		
Uses	Closures		
	Containers		
	Food Containers		
	Household Goods		
Agency Ratings	AS 2070-1999		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.902	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	39.0	MPa	ASTM D638
Flexural Modulus	2100	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	60	J/m	ASTM D256A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT