

E-Pos 328

Epoxy; Epoxide

Epocat Nederland BV

Message:

E-Pos 328 is a medium viscosity epoxy resin, based on bisphenol A and epichlorohydrin. E-Pos 328 does not contain any diluent. E-Pos 328 exhibits superior mechanical and chemical resistance properties and an excellent resistance to heat.

Product applications

E-Pos 328 is used at room temperature in combination with amine-based curing agents in the formulation of two-component systems.

E-Pos 328 can be used in civil engineering applications such as floorings, mortars or solventfree adhesives. It can also be used in composites and in electrical and electronic applications.

General Information		
Features	Good Chemical Resistance	
	High Heat Resistance	
	Medium Viscosity	
Uses	Adhesives	
	Electrical/Electronic Applications	
	Flooring	
Agency Ratings	EC 1907/2006 (REACH)	
Physical	Nominal Value	
Gardner Color	< 1.00	
Epoxy Equivalent	184 to 190	g/mol
Uncured Properties	Nominal Value	Unit
Solids Content	100	%
Density (20°C)	1.16	g/cm ³
Viscosity (25°C)	12 to 15	Pa·s

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT