

ChronoFlex® AR 75A

Polyurethane (MDI)
CardioTech International, Inc.

Message:

ChronoFlex® AR 75A is a Polyurethane (MDI) (PUR-MDI) material. It is available in North America for casting.

Important attributes of ChronoFlex® AR 75A are:

Chemical Resistant

High ESCR (Stress Crack Resistant)

Typical applications include:

Medical/Healthcare

Engineering/Industrial Parts

General Information			
Features	Aromatic		
	High ESCR (Stress Crack Resist.)		
	Solvent Resistant		
Uses	Diaphragms		
	Medical/Healthcare Applications		
	Pump Parts		
Agency Ratings	USP Class VI		
Appearance	Amber		
Forms	Pellets		
Processing Method	Casting		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	75		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	51.7	MPa	ASTM D412
Tensile Elongation (Yield)	500	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT