

# Styropor® F 315 E

Expanded Polystyrene

BASF Corporation

## Message:

### Application

For the production of expanded foams having fire characteristics in conformity with:

DIN 4102 - B 1 (flame-retardant)

EN ISO 13501-1-E

### Product description

Expandable polystyrene (EPS) containing uniformly distributed flame retardant (blowing agent: pentane).

For additional information pertaining to the fire behavior please contact the local BASF representative.

Styropor® F 315 E : Production of expanded foam blocks and moldings of wall thickness greater than 8 mm

General Information		
UL YellowCard	E41871-101746625	
Additive	Blowing Agent 3	
	Flame Retardant	
Features	Flame Retardant	
Uses	Foam	
	Insulation	
Agency Ratings	DIN 4102/B1	
	EC 1907/2006 (REACH)	
RoHS Compliance	RoHS Compliant	
Forms	Spheres	
Physical	Nominal Value	Unit
Apparent Density		
-- <sup>1</sup>	0.02	g/cm <sup>3</sup>
--	0.02 to 0.04	g/cm <sup>3</sup>
Sieve Analysis		
< 400.0 µm	< 3.0	%
400.0 to 1120.0 µm	> 92	%
> 1.12 mm	< 5.0	%
Aging - intermediate	0.4 to 2.0	day
Bead Size	700.0 to 1000.0	µm
NOTE		
1.	Achievable in single pre-expansion	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT