

# Delta N66R-4G40

Polyamide 66

Delta Polymers

Message:

Delta N66R-4G40 is a Polyamide 66 (Nylon 66) product filled with 20% glass fiber. It is available in North America. Primary characteristic: impact resistant.

General Information			
Filler / Reinforcement	Glass Fiber,20% Filler by Weight		
Features	High Impact Resistance		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm <sup>3</sup>	ASTM D792
Molding Shrinkage - Flow	0.80	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	111	MPa	ASTM D638
Flexural Modulus	3790	MPa	ASTM D790
Flexural Strength (Yield)	145	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	200	J/m	ASTM D256
Thermal	Nominal Value	Unit	
Melting Temperature	265	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT