

# ADMER™ SE810

Thermoplastic Elastomer

Mitsui Chemicals America, Inc.

Message:

ADMER™ SE810 is a Thermoplastic Elastomer (TPE) material. It is available in North America for cast film.

Typical applications include:

Adhesives/Tapes

Coating Applications

| General Information                       |                      |                   |             |
|---|----------------------|-------------------|-------------|
| Uses                                      | Adhesives            |                   |             |
|   | Coating Applications |                   |             |
| Forms                                     | Pellets              |                   |             |
| Processing Method                         | Cast Film            |                   |             |
| Physical                                  | Nominal Value        | Unit              | Test Method |
| Density                                   | 0.890                | g/cm <sup>3</sup> | ASTM D1505  |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 7.2                  | g/10 min          | ASTM D1238  |
| Thermal                                   | Nominal Value        | Unit              | Test Method |
| Vicat Softening Temperature               | 40.0                 | °C                | ASTM D1525  |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT