Karina STRAW PVC COMPOUND 701-38/

14-F-IS-BZ

Polyvinyl Chloride

Karina Ind. e Com. de Plásticos Ltda

Message:

HEAVY METAL FREE PVC COMPOUND RECOMMENDED FOR PROFILES EXTRUSION. ALSO RECOMMENDED FOR PLUG INJECTION.

General Information			
Uses	Reflectors		
Appearance	Straw		
Processing Method	Injection Molding		
	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Density ¹	1.40 to 1.46	g/cm³	IEC 60811-1-3
Color	ОК		ME 12
Color a	-1.54 to 1.46		ME 12
Color b	7.52 to 10.5		ME 12
Color L	74.7 to 77.7		ME 12
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	68 to 72		NBR 7456

Tensile Strain (Yield)	> 250
NOTE	
1.	24 hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Unit

MPa

%

Test Method

IEC 60811-1-1

IEC 60811-1-1

Nominal Value

> 6.37

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Mechanical

Tensile Stress

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

