

COSMOTHENE® L725

Low Density Polyethylene

TPC, The Polyolefin Company (Singapore) Pte Ltd

Message:

COSMOTHENE® L725 is a Low Density Polyethylene product. It can be processed by extrusion coating and is available in Asia Pacific. Typical application:

Coating Applications.

Characteristics include:

Good Adhesion

Good Processability

Good Sealability

General Information			
Features	Good Adhesion Good Heat Seal Good Processability Low Neck-In		
Uses	Coating Applications		
Forms	Pellets		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.918	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	7.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	13.7	MPa	ASTM D638
Tensile Elongation (Break)	550	%	ASTM D638
Apparent Bending Modulus	216	MPa	ASTM D747
Thermal	Nominal Value	Unit	
Melting Temperature	105	°C	
Extrusion	Nominal Value	Unit	
Melt Temperature	300 to 320	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT