

Hostacom DYS707N HS1 NAT

Polypropylene

LyondellBasell Industries

Message:

Hostacom DYS707N HS1 NAT is an unfilled, impact modified grade that is typically used for automotive pillar applications that require excellent impact/stiffness balance, good flowability, and excellent impact performance at low temperature.

General Information		
Additive	Impact modifier	
Features	Impact modification	
Uses	Car interior parts	
Processing Method	Injection molding	
Physical	Nominal Value	Unit
Density	0.900	g/cm ³
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	18	g/10 min
Mechanical	Nominal Value	Unit
Tensile Strength (Yield)	16.0	MPa
Flexural Modulus	940	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength (23°C)	60	kJ/m ²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT