THERMOLAST® K TF7FMA (Series: FC/AD1)

Thermoplastic Elastomer

KRAIBURG TPE

Message:

The FC/AD1 Series is your material solution for applications with food contact providing excellent adhesion to polar thermoplastics such as PC, ABS and

Typical applications

Function and design elements

Grip applications

Household articles

Packaging (for food and careproducts)

Razors

Seals

Toothbrushes

Toys

Material advantages

Applications with food contact

Code of Federal Regulations, Title 21 (CFR 21) "FDA"

Easy coloring (compounds in natural colors)

EN71/3

Excellent adhesion

Excellent processing behavior

Halogen-free

Regulation (EU) No. 10/2011

General Information				
Features	Food Contact Acceptable			
	Good Adhesion			
	Good Colorability			
	Good Processability			
	Halogen Free			
Uses	Food Packaging			
	Household Goods			
	Non-specific Food Applications			
	Packaging			
	Seals			
	Toothbrush Handles			
	Toys			
Agency Ratings	EN 71-3			
	EU 10/2011			
	FDA Food Contact, Unspecified Rating			
Appearance	Natural Color			
Processing Method	Injection Molding			

Physical	Nominal Value	Unit	Test Method
Density	1.10	g/cm³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	67		ISO 7619
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress ¹ (Yield)	5.00	MPa	ISO 37
Tensile Elongation ² (Break)	550	%	ISO 37
Tear Strength ³	18	kN/m	ISO 34-1
Additional Information	Nominal Value	Unit	Test Method
Adhesion to ABS	10.5	kN/m	Renault D41/1916
Adhesion to PC	14.0	kN/m	Renault D41/1916
Injection	Nominal Value	Unit	
Drying Temperature	60.0 to 80.0	°C	
Drying Time	2.0 to 4.0	hr	
Rear Temperature	180	°C	
Middle Temperature	210	°C	
Front Temperature	240	°C	
Mold Temperature	40.0 to 60.0	°C	
Injection Pressure	20.0 to 100	MPa	
Back Pressure	2.00 to 10.0	MPa	
NOTE			
1.	Type S2, 200 mm/min		
2.	Type S2, 200 mm/min		
3.	Method Bb, Angle (Nicked)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

