

Selvol™ 165

Polyvinyl Alcohol

Sekisui Chemical Company, Ltd.

Message:

Selvol™ 165 is a Polyvinyl Alcohol (PVOH) product. It can be processed by coating and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Selvol™ 165 include coating applications, adhesives/tapes and film. Primary characteristic: eco-friendly/green.

General Information		
Features	Biodegradable	
	Water Soluble	
Uses	Adhesives	
	Coating Applications	
	Film	
	Paper Coatings	
Forms	Granules	
Processing Method	Coating	
Physical	Nominal Value	Unit
Solution Viscosity ¹	62 to 72	mPa · s
Ash Content	< 1.2	wt%
pH - 4% Solution	5.5 to 7.5	
Volatile Matter		
--	< 5.0	wt%
Organic	< 1.0	wt%
Hydrolysis ²	99 to 100	%
Methanol Extractables	< 0.9	wt%
NOTE		
1.	4%	
2.	Mole	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT