

DAPCO™ 3011

Epoxy; Epoxide

Cytec Industries Inc.

Message:

DAPCO™ 3011 is a two-component, fast curing, low density, self-extinguishing epoxy filler.

Suggested Applications:

DAPCO 3011 is commonly used for potting, stiffening and edge filling of honeycomb core.

DAPCO 3011 is also used for aircraft interior repair.

General Information		
Features	Fast Cure	
	Good Adhesion	
	Good Chemical Resistance	
	High Stiffness	
	Low Density	
	Self Extinguishing	
Uses	Adhesives	
	Aerospace Applications	
	Filling Applications	
	Structural Parts	
Appearance	Brown	
Forms	Paste	
Processing Method	Potting	
Hardness	Nominal Value	
Durometer Hardness (Shore D)	65 to 70	
Mechanical	Nominal Value	Unit
Compressive Strength	24.1	MPa
Thermoset	Nominal Value	
Thermoset Components		
Hardener	Mix Ratio by Weight: 13	
Resin	Mix Ratio by Weight: 100	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

