

Hifax TYC 1190P 3004 BLACK

Thermoplastic Polyolefin Elastomer

LyondellBasell Industries

Message:

Hifax TYC 1190P 3004 BLACK high melt flow, 1,600 MPa flexural modulus, mineral-filled thermoplastic elastomeric olefin (TEO) resin has a very good balance of properties and processability. It is typically used for molded-in color automotive bumper fascia applications.

For regulatory compliance information, see Hifax TYC 1190P 3004 BLACK Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS).

General Information			
Features	Good dimensional stability		
	Rigid, good		
	Impact resistance, good		
	Workability, good		
	High liquidity		
Uses	Car anti-collision bar		
	Application in Automobile Field		
	Automotive exterior parts		
Appearance	Black		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.01	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	25	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield, 23°C)	17.0	MPa	ISO 527-2
Tensile Strain (Break, 23°C)	> 500	%	ISO 527-2
Flexural Modulus (23°C)	1600	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	55	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT