

TITANLENE® LDC 800YY

Low Density Polyethylene

Lotte Chemical Titan (M) Sdn. Bhd.

Message:

LDC800YY is a low density polyethylene resin for extrusion coating and is a barefoot grade. LDC800YY meets the U.S. Food and Drug Administration (FDA) criteria for food contact use as specified in 21 CFR 177.1520 (c) 2.1 & (c) 2.2.

APPLICATIONS:

Coating for all substrates.

Characteristics:

Good drawdown, good heat seability and adhesion properties.

General Information			
Features	Good Adhesion		
	Good Drawdown		
	Good Heat Seal		
	Low Density		
Uses	Coating Applications		
Agency Ratings	FDA 21 CFR 177.1520(c) 2.1		
	FDA 21 CFR 177.1520(c) 2.2		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.5	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Oxygen Permeability	2200	cm ³ · mm/m ² /atm/24 hr	ASTM D3985
Water Vapor Transmission Rate (25 µm, 38°C, 90% RH)	18	g · mm/m ² /atm/24 hr	ASTM F372
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	87.0	°C	ASTM D1525
Extrusion	Nominal Value	Unit	
Melt Temperature	270 to 340	°C	
Neck-in ¹ (295°C)	80.0	mm	
NOTE			
1.	constant output 50 m/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

