

Nipolon® Nipolon®

Low Density Polyethylene

TOSOH Corporation

Message:

Nipolon® Nipolon® is a Low Density Polyethylene material. It is available in Asia Pacific, Europe, or North America for blow molding, blown film, extrusion coating, injection molding, or laminating. Primary attribute of Nipolon® Nipolon®: Good Processability.

Typical applications include:

Bags/Liners

Film

Household Applications

Packaging

General Information	
Features	Good Processability
	High Elasticity
	Shock Absorbent
Uses	Film
	Heavy-duty Bags
	Household Goods
	Liners
	Packaging
Appearance	Clear/Transparent
Forms	Pellets
Processing Method	Blow Molding
	Blown Film
	Extrusion Coating
	Injection Molding
	Laminating

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT