# RTP 4000 A AR 15 TFE 15 SI 2

### Polyphthalamide

**RTP** Company

#### Message:

Warning: The status of this material is 'Commercial: Limited Issue' The data for this material has not been recently verified. Please contact RTP Company for current information prior to specifying this grade. -Preliminary Product Data per RTP Co.-

General Information				
Filler / Reinforcement	Aramid fiber, 15% filler by w	Aramid fiber, 15% filler by weight		
Additive	PTFE lubricant (15%)			
	Silicone lubricant (2%)			
Features	Lubrication			
RoHS Compliance	Contact manufacturer			
Appearance	Black			
	Natural color			
Forms	Particle			
Processing Method	Injection molding	Injection molding		
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.30	g/cm³	ASTM D792	
Molding Shrinkage - Flow (3.18 mm)	0.50	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	5860	MPa	ASTM D638	
Tensile Strength	89.6	MPa	ASTM D638	
Tensile Elongation (Break)	2.0	%	ASTM D638	
Flexural Modulus	4480	MPa	ASTM D790	
Flexural Strength	138	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (3.18 mm)	27	J/m	ASTM D256	
Unnotched Izod Impact (3.18 mm)	270	J/m	ASTM D4812	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity	1.0E+15	ohms·cm	ASTM D257	
Additional Information				
Mold Shrinkage, Linear-Flow, ASTM D955	5, 0.25in.: 6mil/in.Tensile Elongation,	ASTM D638: 2-3%		
Injection	Nominal Value	Unit		
Rear Temperature	304 - 343	°C		
Middle Temperature	304 - 343	°C		
Front Temperature	304 - 343	°C		

Mold Temperature	110 - 149	°C
Injection Pressure	68.9 - 103	MPa

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

