

megol® ANTISTATIC 63

Styrene Ethylene Butylene Styrene Block Copolymer

API SpA

Message:

megol®ANTISTATIC 63 is a styrene-ethylene-butylene-styrene block copolymer (SEBS) product. It can be processed by injection molding and is available in Europe.

Features include:

Copolymer

good weather resistance

General Information			
Features	Block Copolymer		
	Antistatic property		
	Ozone resistance		
	Good weather resistance		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.00	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	63		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus			ASTM D638
100% secant	1.80	MPa	ASTM D638
300% secant	2.60	MPa	ASTM D638
Tensile Strength	8.50	MPa	ASTM D638
Tensile Elongation (Break)	830	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	25.0	kN/m	ASTM D624
Additional Information			

Ozone, 72 hr, 40°C, 200 ppcm, 20% tension: Excellent

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

