# Ebalta GM 976 / PUR 1

## Polyurethane

## Ebalta Kunststoff GmbH

#### Message:

ebalta GM 976 is an easy-to-handle-2 components-polyurethane casting compound which shows very low adhesive properties compared to moulding sand. Due to its very high abrasion resistance, GM 976 is especially suitable for foundry patterns, which have to resist to abrasive wear by moulded sand. GM 976 even keeps its high mechanical strength when using moulding sands with higher temperatures.

Applications Core boxes Foundry pattern well castable Properties abrasion resistant good compressive strength

General Information			
Features	Good Abrasion Resistance		
	Good Compressive Strength		
Appearance	Green		
Processing Method	Casting		
Hardness	Nominal Value		Test Method
Shore Hardness (Shore D)	85 to 91		ISO 7619
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	5030 to 5530	MPa	ISO 178
Flexural Stress	70.0 to 80.0	MPa	ISO 178
Compressive Stress	80.0 to 90.0	MPa	ISO 604
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	8.0 to 12	kJ/m²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	67.0 to 71.0	°C	ISO 75-2/B
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Weight: 30		
Resin	Mix Ratio by Weight: 100		
Uncured Properties	Nominal Value	Unit	
Density (20°C)	1.55 to 1.65	g/cm³	
Viscosity (25°C)	3.5 to 4.5	Pa·s	
Curing Time (20°C)	4.0 to 10	hr	
Pot Life <sup>1</sup> (20°C)	25 to 35	min	
NOTE			
1.	200 g		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

