

# Nipol® LX430

Latex  
Zeon Corporation

Message:

Latex of styrene-butadiene copolymer (SB latex)  
Characteristics  
Slightly hard carboxyl SB latex. Excellent stability, filler dispersion and adhesiveness. Easy processing due to low bubbling.  
Excellent adhesive strength and stability. Low bubbling. Available for various purposes.  
Applications  
Special papers used as battery separators and in paper processing (impregnated).  
Adhesives for wood.

General Information			
Features	Copolymer		
	Good Adhesion		
	Good Processability		
	Good Stability		
	Medium Hardness		
Uses	Adhesives		
Physical	Nominal Value	Unit	
Solution Viscosity	130	mPa · s	
Average Particle Size	150	nm	
pH	7.0		
Surface Tension	50	mN/m	
Total Solids	49	%	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	12.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT