Haysite Plastics HCR-196

Thermoset Polyester

Haysite Reinforced Plastics

Message:

Haysite Plastics HCR-196 is a Thermoset Polyester product. It is available in North America.

Characteristics include:

Chemical Resistant

Corrosion Resistant

General Information			
Features	Good Chemical Resistance Good Corrosion Resistance		
Appearance	Grey		
Forms	Sheet		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.70	g/cm³	ASTM D792
Water Absorption (Equilibrium)	0.20	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Barcol Hardness	55		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹	70.3	MPa	ASTM D638
Flexural Strength ²	155	MPa	ASTM D790
Compressive Strength ³	207	MPa	ASTM D695
Shear Strength	93.8	MPa	ASTM D229
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact ⁴	430	J/m	ASTM D256
Electrical	Nominal Value	Unit	Test Method
Dielectric Strength ⁵ (Air/Oil)	16	kV/mm	ASTM D149
Dielectric Strength - in Air/Oil ⁶	47000	V	ASTM D149
NOTE			
1.	Lengthwise		
2.	Lengthwise		
3.	Flatwise		
4.	Lengthwise		
5.	Perpendicular		
6.	Parallel		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

