

KER® 1904

Rubber

Synthos S.A.

Message:

KER® 1904 is a grade of high-styrene rubber. It is produced by mixing of styrene-butadiene latex and high styrene resin in adequate proportion. It is coagulated by a system of acid and synthetic coagulant, is stabilized with a nonstaining antioxidant and contains abt. 68% of bonded styrene.

APPLICATION

KER® 1904 is used for production of floor finishes, cables, toys and micro porous rubber for footwear industry.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
Uses	Flooring		
	Footwear		
	Toys		
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Ash Content	< 0.4	wt%	ASTM D5667
Organic Acid	5.0 to 7.0	wt%	ASTM D5774
Soap	< 0.4	wt%	ASTM D5774
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

