

ZELAS® MC638

Thermoplastic Elastomer
Mitsubishi Chemical Performance Polymers, Inc.

Message:

ZELAS® MC638 is a Thermoplastic Elastomer (TPE) material. It is available in Asia Pacific, Europe, or North America for extrusion.
Typical application of ZELAS® MC638: Medical/Healthcare

General Information			
Uses	Medical/Healthcare Applications		
Agency Ratings	JP XV		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.890	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.0	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2
Yield	19.0	MPa	
Break	36.0	MPa	
Nominal Tensile Strain at Break	720	%	ISO 527-2
Flexural Modulus	600	MPa	ISO 178
Flexural Stress	19.0	MPa	ISO 178
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	125	°C	ISO 11357-3
Optical	Nominal Value	Unit	Test Method
Haze (2000 μm)	40	%	ISO 2813

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT