

Alloy Exchange Reprocessed PC001

Polycarbonate + ABS

Alloy Exchange, Inc.

Message:

Alloy Exchange Reprocessed PC001 is a Polycarbonate + ABS (PC+ABS) material. It is available in North America. Primary attribute of Alloy Exchange Reprocessed PC001: Eco-Friendly/Green.

General Information			
Recycled Content	Yes		
Appearance	Black		
	Grey		
Forms	Pellets, Reprocessed		
Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	1.12	g/cm ³	ASTM D792A
Melt Mass-Flow Rate (MFR) (230°C/3.8 kg)	2.9	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (3.29 mm)	47.8	MPa	ASTM D638
Tensile Elongation (Break, 3.29 mm)	20	%	ASTM D638
Flexural Modulus - Tangent (3.28 mm, 50.0 mm Span)	2280	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact ² (3.22 mm)	500	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load ³ (1.8 MPa, Unannealed)	98.0	°C	ASTM D648A
NOTE			
1.	No. of specimens tested: 3		
2.	No. of specimens tested: 5		
3.	No. of specimens tested: 2		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT