SHIN-A SEY-175APM75

Epoxy; Epoxide

SHIN-A T&C;

Message:

lsocyanate-Modified Epoxy (Halogen-Free) Solvent: Acetone/PM Features: Br Free, Tg = 160 - 170°C (Var.)

| General Information | | |
|---------------------|------------------------|------|
| Features | Bromine Free | |
| | Halogen Free | |
| | | |
| Uses | Adhesives | |
| | Coating Applications | |
| | Paint | |
| | Printed Circuit Boards | |
| | | |
| Physical | Nominal Value | Unit |
| Viscosity (25°C) | < 3.00 | Pa·s |
| Epoxy Equivalent | 260 to 310 | g/eq |
| N.V. | 74.0 to 76.0 | wt% |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

