Shandong PA610 A6G6301

Polyamide 610

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA610 A6G6301 is a Polyamide 610 (Nylon 610) material filled with filler. It is available in Asia Pacific.

 $Important\ attributes\ of\ Shandong\ PA610\ A6G6301\ are:$

Good Dimensional Stability

Good Processability

Heat Resistant

High Stiffness

High Strength

General Information		
Filler / Reinforcement	Filler	
Features	Good Dimensional Stability	
	Good Processability	
	Good Wear Resistance	
	High Heat Resistance	
	High Stiffness	
	High Strength	
	Low to No Water Absorption	

Physical	Nominal Value	Unit
Ash Content	30	%
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	114	MPa
Tensile Strain (Break)	5.0	%
Flexural Modulus	5100	MPa
Flexural Stress	155	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	27	kJ/m²
Charpy Unnotched Impact Strength	91	kJ/m²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

