

Shuman PE 603

Polyethylene
Shuman Plastics, Inc.

Message:
POLYETHYLENE 603 BLACK
OFFERS THIS COMBINATION OF PROPERTIES:
HIGH DENSITY, INJECTION MOLDING GRADES, GOOD CHEMICAL RESISTANCE

General Information			
Features	Good Chemical Resistance		
	High Density		
Appearance	Black		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.950	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	2.0 to 18	g/10 min	ASTM D1238
Injection	Nominal Value	Unit	
Processing (Melt) Temp	182 to 210	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT