

Vexel B12GF15

Polybutylene Terephthalate

Custom Resins Group

Message:

General purpose 15% glass fiber reinforced PBT polyester resin
Has the high chemical and heat resistance of PBT combined with improved strength and stiffness
Suitable for brackets, levers, electrical connectors, housings and other similar uses

General Information	
Filler / Reinforcement	Glass Fiber,15% Filler by Weight
Features	General Purpose
	Good Chemical Resistance
	Good Stiffness
	Good Strength
	High Heat Resistance
Uses	Connectors
	General Purpose
	Housings

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.50 to 0.70	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	89.6	MPa	ASTM D638
Flexural Modulus	4480	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	48	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	207	°C	
1.8 MPa, Unannealed	188	°C	
Peak Melting Temperature	227	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

