Thermoset Plastics DC-441

Epoxy; Epoxide

Thermoset, Lord Chemical Products

Message:

Thermoset Plastics DC-441 is an Epoxy; Epoxide (Epoxy) material filled with aluminum. It is available in North America for casting. Primary attribute of Thermoset Plastics DC-441: Heat Resistant.

General Information			
Filler / Reinforcement	Aluminum		
Features	Good Thermal Stability		
Forms	Pellets		
Processing Method	Casting		
Physical	Nominal Value	Unit	Test Method
Apparent Density	1.69	g/cm³	ASTM D1895
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	47.2	МРа	ASTM D638
Flexural Strength (Yield)	92.4	МРа	ASTM D790
Compressive Strength	228	MPa	ASTM D695
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
	Mix Ratio by Volume: 1.0		
Hardener	Mix Ratio by Weight: 8.0		
	Mix Ratio by Weight: 100		
	, 3		
	M' D '' M 75		
Resin	Mix Ratio by Volume: 7.5		ACT: 1 70000
Thermoset Mix Viscosity (25°C)	8000	сР	ASTM D2393
Demold Time			
25°C	960 to 1400	min	
121°C	120	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

