

Nipol® LX874

Latex
Zeon Corporation

Message:

Acrylate latex
Characteristics
Extremely soft with good waterproofing properties and dry cleaning resistance.
Applications
Spiral spring supporting sheets of automobile seats, filters, clothing materials, clothing, and automobile ceiling materials.
Paper processing (filters), and tape paper (impregnated).
Fire hoses (impregnated).

General Information			
Features	Copolymer		
	Crosslinkable		
	Soft		
Uses	Automotive Applications		
	Filters		
	Hose		
Physical	Nominal Value	Unit	
Solution Viscosity	20	mPa·s	
pH	6.5		
Surface Tension	26	mN/m	
Total Solids	45	%	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-31.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT