

Sinpolene MBB2671

Linear Low Density Polyethylene
Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB2671 is a polyethylene-based black masterbatch designed specifically for use in tubular film blowing, geomembranes, blow moulding, injection moulding, and sheet extrusion of polyolefins. SINPOLENE MBB2671 has very high pigment loading and thus offers high coloring value with superior quality and performance.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General Information			
Features	General		
Uses	Packaging		
Forms	Particle		
Processing Method	Blow film		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (200°C/21.6 kg)	< 50	g/10 min	ASTM D1238
Carbon Black Content	50	%	ASTM D1603
Moisture Content			ASTM D3030
Additional Information			

Recommended dosage: 2 - 5%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

