

Axiall PVC 9175 White 10

Rigid Polyvinyl Chloride

Axiall Corporation

Message:

Axiall PVC 9175 White 10 is a rigid PVC material. This product is available in North America and is processed by blow molding.

General Information			
Appearance	White		
Forms	Particle		
Processing Method	Blow molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.34	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2860	MPa	ASTM D638
Tensile Strength (Yield)	50.3	MPa	ASTM D638
Flexural Strength	89.6	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
3.18 mm	27	J/m	ASTM D256
6.35 mm	16	J/m	ASTM D256
Tensile Impact Strength	120	kJ/m ²	ASTM D1822
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	55.0	°C	ASTM D648
Additional Information			

Equilibrium Torque, Brabender Plastograph, No. 6 Roller Head, 190°C Bath, 57 g Charge; 60/43 rpm: 925 m-gStability Time, Brabender Plastograph, No. 6 Roller Head, 190°C Bath, 57 g Charge; 60/43 rpm: 61 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT