

# Dryflex® C1 5065

Thermoplastic Elastomer

ELASTO

## Message:

The C1 Series consists of materials in natural colours that can easily be coloured. The compounds have a permanent antistatic / ESD effect and a surface resistivity down to  $10^8$  Ohm.

General Information	
Additive	Antistatic
Features	Antistatic
	ESD Protection
	Good Colorability
Appearance	Natural Color
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Density	0.930	g/cm <sup>3</sup>	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	65		ISO 868
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	4.20	MPa	ISO 37
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	3.0E+8	ohms	IEC 60093

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

