Epic Epoxy S7151

Epoxy; Epoxide

Epic Resins

Message:

Epic S7151 is a two component general purpose epoxy potting/casting compound. S7151 is an excellent choice for many potting applications and features a meter-mix friendly 3:1 mix ratio by volume, very low shrinkage and good adhesion to both metal and plastic cases. S7151 retains a high gloss in the cured state resulting in very attractive parts.

General Information					
Features	Highlight				
	Good adhesion				
	Low shrinkage				
	General				
Uses	Electrical/Electronic Applications				
	Electronic insulation				
	General				
RoHS Compliance	RoHS compliance				
Processing Method	Enclosure				
	potting				
	Casting				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.45 - 1.47	g/cm³	ASTM D792		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D, 25°C)	83 - 87		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Glass Transition Temperature	39.0 - 43.0	°C	ASTM E1356		
CLTE - Flow	6.1E-5 - 6.7E-5	cm/cm/°C	ASTM D696		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity	9.8E+13 - 1.0E+14	ohms·cm	ASTM D257		
Dielectric Strength (2.54 mm)	17 - 19	kV/mm	ASTM D149		
Dielectric Constant (100 kHz)	3.67 - 4.05		ASTM D2520		
Dissipation Factor (100 kHz)	0.013 - 0.015		ASTM D150		
Thermoset	Nominal Value	Unit	Test Method		
Thermoset Components					

Mixing	ratio	by	capacity:	3.0

Component a	Mixing ratio by weight: 100
	Mixing ratio by capacity: 1.0

Component B	Mixing ratio by weight: 20	Mixing ratio by weight: 20		
Pot Life ¹ (25°C)	80 - 120	min		
Thermoset Mix Viscosity (25°C)	< 3000	сР	ASTM D2393	
NOTE				
1.	200 Gram Mass			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

