

Hostacom RE44AC

Thermoplastic Polyolefin Elastomer

LyondellBasell Industries

Message:

Hostacom RE44AC Black precolored, medium melt flow, 700 MPa flexural modulus thermoplastic elastomeric olefin (TEO) resin has a good combination of properties. It is a compounded product containing post-industrial or post-consumer recycled polypropylene and reactor grade TEO. It was designed primarily for black automotive utility-type applications.

General Information			
Recycled Content	Yes		
Uses	Automotive Applications		
	Automotive Under the Hood		
Appearance	Black		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	11	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	17.0	MPa	ISO 527-2
Flexural Modulus	700	MPa	ISO 178

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

