

Qenos PP PPK 1060

Polypropylene Homopolymer

Qenos Pty Ltd

Message:

PPK 1060 is a low flow Polypropylene homopolymer.
PPK 1060 is suitable for extrusion of pipe, film and tape, as well as the production of blown bottles for fruit juice and pharmaceutical use. Suitability for use in any application should be determined by appropriate performance testing.
PPK 1060 is suitable for food contact applications and conforms to the requirements of AS2070-1999, Plastics Materials for Food Contact Use.

General Information	
Features	Food Contact Acceptable
	Homopolymer
	Low Flow
Uses	Bottles
	Film
	Fruit Juice Bottles
	Pharmaceuticals
	Piping
	Tape
Agency Ratings	AS 2070-1999
Forms	Pellets
Processing Method	Blow Molding
	Extrusion
	Pipe Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.905	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)			ASTM D1238
230°C/2.16 kg	1.0	g/10 min	
230°C/5.0 kg	5.0	g/10 min	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	41.0	MPa	ASTM D638
Flexural Modulus	1600	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	190	J/m	ASTM D256A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

