Sinpolene MBB1406

Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB1406 is a polyethylene-based black masterbatch designed specifically for use in tubular film blowing, blow moulding, injection moulding, and sheet extrusion of polyolefins. SINPOLENE MBB1406 has very high pigment loading and thus offers high coloring value with superior quality and performance.

* Easy processing

- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General Information	
Features	General
Uses	Packaging
	Films
	Sheet
RoHS Compliance	RoHS compliance
Forms	Particle
Processing Method	Blow film
	Sheet extrusion molding

Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.16	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (190°C/2.16				
kg)	< 25	g/10 min	ASTM D1238	
Carbon Black Content	45	%	ASTM D1603	
Moisture Content		%	ASTM D3030	
Additional Information				

Recommended dosage: 1 - 5%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com No. 215, Lianhe North Road, Fengxian District, Shanghai, China

