

# INDURE™ X210

Thermoplastic Polyolefin Elastomer

LyondellBasell Industries

## Message:

Indure X210 engineered polyolefin material is designed for large, molded-in-color automotive applications that require ductile impact properties at low temperatures as well as processability.

Typical Customer Applications:

Exterior Applications, Bumpers

General Information			
Features	Ductile		
	Good Processability		
	Scratch Resistant		
Uses	Automotive Applications		
	Automotive Bumper		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.970	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	40	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress <sup>1</sup> (Yield)	24.0	MPa	ISO 527-2/50
Flexural Modulus	1550	MPa	ISO 178
NOTE			
1.	150x10x4 mm specimen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT