

Indothene LL 36RA045

Linear Low Density Polyethylene
Reliance Industries Limited

Message:

Indothene LL 36RA045 is a Linear Low Density Polyethylene product. It can be processed by rotational molding and is available in Africa & Middle East or Asia Pacific.

General Information			
Forms	Granules		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.936	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	4.5	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	17.7	MPa	ASTM D638
Tensile Elongation (Yield)	20	%	ASTM D638
Flexural Modulus	588	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	540	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	117	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT