

TABOND 5010

Polypropylene

SILON s.ro

Message:

Tabond 5010 is a chemically modified Polypropylene. This grade is for sheets and bottles composed of Polypropylene (PP) and EVOH or PA.

General Information			
Features	Durable		
	Good Adhesion		
Uses	Adhesives		
	Bonding		
	Plastics Modification		
Appearance	White		
Forms	Pellets		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	
Density	0.902	g/cm ³	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.3	g/10 min	
Hardness	Nominal Value	Unit	
Shore Hardness (Shore D, 15 sec)	66		
Mechanical	Nominal Value	Unit	
Tensile Stress (Yield)	31.6	MPa	
Tensile Strain (Break)	> 360	%	
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	161	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT