

Weifang Kingdom CPE135A

Chlorinated Polyethylene

Weifang Kingdom Plastic Co., Ltd

Message:

FEATURES: This product is a random and saturated thermoplastic resin. It has very good extruding flowability when blended with PVC.

APPLICATION: This product is suitable for rigid PVC products and compression moulding products.

General Information			
Features	Flame Retardant		
	Good Chemical Resistance		
	Good Flexibility		
	Good Flow		
	Good Processability		
	Good Weather Resistance		
	High Heat Resistance		
	High Molecular Weight		
	Low Temperature Flexibility		
	Low Temperature Resistant		
	Low to No Taste		
Uses	Film		
	Fittings		
	Piping		
	Plastics Modification		
	Profiles		
	Sheet		
	Wire & Cable Applications		
Appearance	White		
Forms	Powder		
Processing Method	Compression Molding		
	Extrusion		
Physical	Nominal Value	Unit	Test Method
Chlorine Content	34.0 to 36.0	wt%	GB/T 9872
Hardness	Nominal Value	Unit	Test Method
Shore Hardness	< 56		GB/T 531
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength	> 8.00	MPa	GB/T 528
Tensile Elongation (Break)	> 700	%	GB/T 528

Thermal	Nominal Value	Unit	Test Method
Heat of Fusion	< 2.00	J/g	DSC
Volatiles	< 0.40	%	GB/T 2914

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

