

Beamset 730

Acrylic

Arakawa Chemical Industries, Ltd.

Message:

This resin is a photo-curable resin that quickly and three-dimensionally cures by radical polymerization that occurs with electron beam (EB) or ultraviolet ray (UV) irradiation. This resin has been used widely for various applications.

Type:

Di-trimethylolpropane tetraacrylate

Characteristics:

Good compatibility

Excellent hardness

Low P.I.I.

Low Viscosity

Use:

Hard coatings

Ink

General Information		
Features	High Hardness	
	Low Viscosity	
Uses	Coating Applications	
Appearance	Transparent - Slight Yellow	
Forms	Liquid	
Additional Information	Nominal Value	Unit
Functionality	4.00	
Non-Volatile Content	100	%
Uncured Properties	Nominal Value	Unit
Viscosity (25°C)	0.40 to 0.60	Pa·s

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT