

# Yanshan PE LD605

Low Density Polyethylene  
SINOPEC Beijing Yanshan Petrochemical

Message:

Yanshan PE LD605 is a Low Density Polyethylene product. It can be processed by film extrusion or injection molding and is available in Asia Pacific. Typical application: Film.


General Information			
Uses	Film		
Processing Method	Film Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.922	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR)	6.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	8.00	MPa	ASTM D638
Tensile Elongation (Break)	100	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	86.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT