

# NEOFLON™ NP-120

Perfluoroethylene Propylene Copolymer

DAIKIN AMERICA, INC.

## Message:

NEOFLON FEP is melt processable perfluoro co-polymer of tetrafluoroethylene and hexafluoropropylene.

FEP has excellent electrical properties like PTFE because FEP consists of only fluorine atoms and carbon atoms. The chemical resistance capability and mechanical characteristics are the same as ones of PFA, however the heat resistance is lower than PFA.

## Features

Stress crack resistance is improved from NP-20. Wide range of applications, from thin-walled to thick-walled wire coating.

General Information		
Features	Copolymer	
	Good electrical performance	
Uses	Wire sheath	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR)	4.0 - 10	g/10 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

