

Roscom PVC 201LFR-65 Natural

Flexible Polyvinyl Chloride

Roscom, Inc.

Message:

ROSCOM PVC 201LFR-65 is a flexible vinyl designed for both extrusion and injection molding. This compound carries the UL V-O rating and features high heat stability and lubrication for trouble-free, consistent processing, with a high gloss finish. Typical applications range from automotive parts, key tags and extruded tubing and profiles.

General Information	
Features	Good Flexibility Good Processability Good Thermal Stability High Gloss Lubricated
Uses	Automotive Applications Profiles Tubing
Appearance	Natural Color
Processing Method	Extrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24 to 1.28	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	50 to 80		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	3.79	MPa	ASTM D412
Tensile Strength (Yield)	11.7	MPa	ASTM D412
Tensile Elongation (Break)	480	%	ASTM D412
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-40.0	°C	ASTM D412
Flammability	Nominal Value		Test Method
Flame Rating	V-0		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

