

Evolve™-H SP50800P

High Density Polyethylene

Prime Polymer Co., Ltd.

Message:

Evolve™-H SP50800P is a High Density Polyethylene product. It is available in Asia Pacific, Europe, or North America. Typical application: Additive/Masterbatch. Primary characteristic: high flow.

General Information			
Features	Bimodal Molecular Weight Distribution		
	High Flow		
Uses	Masterbatch		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Density	0.951	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	140	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	124	°C	ISO 11357-3, ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

