

ELASTOSIL® E 60

Silicone

Wacker Chemie AG

Message:

Silicone Rubber, RTV-1

Baking Molds, Household Appliances

Baking Tray Coating, Food Processing

Baking Tray Coating, Paints & Coatings

| General Information | | | |
|---------------------------------------|-------------------------|-------------------|-------------|
| Features | Food Contact Acceptable | | |
| Uses | Coating Applications | | |
| Uncured Properties | Nominal Value | Unit | Test Method |
| Color | Red | | |
| Density | | | |
| -- | 1.12 | g/cm ³ | DIN 53217 |
| -- | 1.13 | g/cm ³ | ISO 1183 |
| Viscosity | 70 | Pa·s | Brookfield |
| Curing Time | 12 | hr | |
| Skin Forming Time ¹ (23°C) | 15.0 to 20.0 | min | |
| Cured Properties | Nominal Value | Unit | Test Method |
| Shore Hardness (Shore A) | 35 | | DIN 53505 |
| Tensile Strength | 2.80 | MPa | DIN 53504 |
| Tensile Elongation at Break | 280 | % | DIN 53504 |
| NOTE | | | |

1. 50% R.H

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT