PolyFR™ JJAZZ

Polyolefin

JJI Technologies, LLC

Message:

JJAZZ® flame retardant is a highly efficient and most unique amino phosphate flame retardant system, based on proprietary catalyst technology and designed for use in environmentally friendly plastics applications. JJAZZ® flame retardant is non-toxic and non-corrosive, offers excellent hydrolytic stability, has superior char forming and low smoke characteristics and is easy to UV stabilize. JJAZZ® flame retardant does not contain any heavy metal or gaseous halogen by products and is compatible in most textile compositions. The most recognizable feature of the JJAZZ® flame retardant is its self-contained catalyst system, thus allowing for an overall lower FR use level and an improved physical property profile to the composition. Applications

Polyolefin plastics where efficiency is a key consideration.

Solvent based coatings, adhesives and paints

Epoxy compounds & Composite Materials

Elastomeric Rubber applications

In most applications loading levels of 20-35% achieve UL 94 V0 ratings (1/16" burn bar).

Materials using JJAZZ® have also met the following standards: ASTM E84, ISO 6722, UL 94 5V, UL VTMO, MVSS302, UL1581(VW-1)

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
	Hydrolytically Stable		
	Low Smoke Emission		
	Non-Corrosive		
	Non-Toxic		
Uses	Adhesives		
	Coating Applications		
	Compounding		
	Paint		
Agency Ratings	ASTM E 84		
	ISO 6722		
	UL 1581		
Appearance	White		
Forms	Powder		
Physical	Nominal Value	Unit	
Specific Gravity	1.30	g/cm³	
Apparent Density	0.40	g/cm³	
Decomposition Temperature - 5%			
Nitrogen	> 240	°C	
рН	7.2		
Flammability	Nominal Value		Test Method

Flame Rating VTM-0 UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT